



FICHA TÉCNICA ALTRO STRONGHOLD 30 / K30

Suelos de seguridad




Monsoon K30153



Dolphin K3010




Abyss K3001



Skyline K30332



Oyster K30215




Surf K30412




Lagoon K30910




Midnight K30421




Maple K30522



Camel K3017



Russet K30262



Tundra K30500



Velvet K30365



Typical Applications:

Kitchens. Canteens. Food preparation and service areas. Areas where grease, oils or fats are present.

Zonas de instalación recomendadas:

Cocinas. Cafeterías. Zonas de preparación y servicio de alimentos. Zonas donde se trabaje con aceite o grasa

Typische Anwendungsbereiche:

Küchen. Kantinen. Lebensmittelzubereitung und Servicebereiche. Bereiche, in denen mit Schmiermitteln, Ölen oder Fetten gearbeitet wird.


Looks great with:

Resultados espectaculares con:

Harmoniert besonders in Kombination mit:

Altro Whiterock White™

Altro Whiterock Satins™

Altro Classic™ 25

Slip resistance / Resistencia al deslizamiento / Rutschfestigkeit

Tested with / Testado con / Getestet mit:

Water / Agua / Wasser

Greasy water / Agua con grasa / Öliges Wasser

Flour / Harina / Mehl

Vegetable Oil / Aceite vegetal / Pflanzenöl

Milk / Leche / Milch

Plastic wrapping / Envoltorio de plástico / Plastikverpackung

 Technical information / Información técnica / Technische Informationen

Flooring type Tipo de pavimento Belagsart	Slip resistance Resistencia al deslizamiento Rutschsicherheit	Thickness Espesor total Gesamtdicke	Weight Peso Flächengewicht	Roll dimensions Dimensiones del rollo Rollenabmessungen	Fire performance Reacción al fuego Brandverhalten
EN 13845 EN 13553	TRRL / CTE EN 13845 EN 13893 DIN 51130	EN 428	EN 430	EN 426	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2
Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag	≥ 55 Class 3 / Clase 3 / Klasse 3 (CTE) ESF DS R12	3 mm	3.9 kg/m ²	2 m x 15 m = 30 m ²	Bfl s1 ≥ 8kw/m ² pass, conforme, bestanden
<p> For further technical information please visit www.altro.com / www.asf.com.au Si desea obtener más información técnica, visite www.altroscandess.com Weitere technische Informationen finden Sie auf unserer website www.altro.de</p>					


 Sustainability / Sostenibilidad / Nachhaltigkeit

Altro are the first safety flooring manufacturer to recycle traditional safety flooring in-house



A+ BRE generic green guide rating for safety flooring, full details available at www.thegreenguide.org.uk



EN13845

Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.


Installation and Maintenance

All Installations in accordance with Altro safety flooring instructions and local codes of practice. Please refer to Altro cleaning card for maintenance advice. Failure to install and maintain Altro flooring in accordance with installation instructions can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber.

Caution

ketone / aromatic solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. Certain chemicals may cause staining of vinyl.

Light Reflectance Values measured in accordance with BS5493:2008 . Exact material match with samples cannot be guaranteed. No podemos garantizar que el material del suelo de seguridad coincida exactamente con el de las muestras. Eine exakte Übereinstimmung des materials mit mustern kann nicht garantiert werden. All information is correct at the time of print and is subject to change without prior notice.

WWW.MELAVINYL.COM



MELAVINYL
CONSTRUYE

PISO HOMOGÉNEO

Dirección: Calle Juan Roberto Acevedo 210 - Pueblo Libre

Correo: Melavinyl.ventas@gmail.com

Telefono: 921-543-278 / 929-198-212

Para más información visite www.melavinyl.com

www.melavinyl.com

