

En pisos vinílicos, la categoría PUR (poliuretano reforzado) se refiere a un tratamiento superficial que proporciona mayor protección, resistencia y durabilidad al piso. Este tratamiento mejora la resistencia a las manchas, la facilidad de limpieza y prolonga la vida útil del piso



DESCRIPTION

Total thickness	ISO 24346 (EN 428)	mm	1.5*	2
Weight	ISO 23997 (EN 430)	g/m ²	2500	3300
Width / Length of sheet	ISO 24341 (EN 426)	cm / lm	200 / 20	

CLASSIFICATION

Norm / Product specification	-	-	ISO 10581(EN 649)	
European classification	ISO 10874 (EN 685)	class	23 - 31 / 34 - 43	
Fire rating	EN 13 501-1	class	Bfl-s1	
Static electrical propensity	EN 1815	KV	<2	
Electrical resistance	EN 1081	Ω	10 ⁹ -10 ¹⁰	
Slip resistance dry	EN 13893	-	≥0.3	
Slip resistance wet	DIN 51130	class	R9	

PERFORMANCES

Wear resistance	EN 660.2	mm ³	≤7.5	
Wear group	EN 649	group	M	
Type binder content	ISO 10581	type	II	
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4	
Residual indentation	ISO 24343-1 (EN 433)	mm	≈0.05	
Castor chair test	ISO 4918 (EN 425)	-	OK	
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	≈0.25	
Colour fastness	ISO 105 - B02	degree	≥ 6	
Chemical products resistance	ISO 26987 (EN 423)	-	OK	
Anti-bacterial and fungicidal treatment	-	-	OK	
Surface treatment	-	-	PUR Protect	
Color number	-	-	22	

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000 - 6	µg/m ³	< 10	
Certification	-	-	Floorscore®	

CE MARKING

CE	EN 14041	-		
----	----------	---	---	--

* Special order, minimum quantities needed

MIPOLAM® 150 is a durable, high performing flexible homogeneous multipurpose flooring suitable for most types of heavy traffic areas. It benefits from PUR Protect surface treatment with excellent cleaning characteristics, improved resistance to scratching and scuffing. MIPOLAM® 150 is recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required.

Don't forget our complementary ranges!



Handrails



Wall Coverings
& Protections



Entrance mats



Skirtings
& Profiles

MIPOLAM® 150, LESS SPEAKING FOR MORE ACTIONS



COMPOSITION
100% REACH compliant
FREE of formaldehyde
FREE of heavy metals
FREE of solvent



RECYCLED CONTENT
25% average
recycled content
100% REACH compliant
recycled content



RECYCLABILITY
100% recyclable
product



INDOOR AIR QUALITY
TVOC emissions between
10 and 100 times better than
norms requirements
Floorscore certified
No formaldehyde emission



INSTALLATION
Innovative adhesive
free installation systems



WELLNESS
Health: Antibacterial activity
(inhibits growth > 99%)



PISO HOMOGÉNEO

Dirección: Calle Juan Roberto Acevedo 210 - Pueblo Libre

Correo: MelavinyL.ventas@gmail.com

Telefono: 921-543-278 / 929-198-212

Para más información visite www.melavinyL.com

www.melavinyL.com

